

RECHARGEABLE

LXPR-5522GMX

# NIGHTSTICK PERMISSIBLE RECHARGEABLE



## DUAL SWITCHES

Easily operate **independent flashlight and floodlight**, or simultaneous in Dual Light™ mode.

IP-67  
DUST/WATER  
PROOF

ZONE 0

## MAGNETS

Rare earth magnets in the tail and on the pocket clip **provide hands-free operation.**



An **soft, unfocused floodlight** is integrated into the housing, perfect for close-up illumination.



**Dual body switches** are perfectly placed for easy one-handed operation, even with gloves.



**Integrated magnets in handle base and the pocket clip** provide options for limitless hands-free usage.



400 LUMENS

## PRODUCT SPECIFICATION SHEET

### ITEM NUMBER/UPC

- LXPR-5522GMX - 017398805643

### CERTIFICATIONS

- CE, cETLus, ATEX, IECEX, MSHA, UKCA, INMETRO

### CASE MATERIAL

- ABS polymer

### LUMENS/RUNTIME

#### SPOTLIGHT

- HIGH: 240L, 8 hrs. runtime

#### FLOODLIGHT

- HIGH: 175L, 8.5 hrs. runtime

#### DUAL-LIGHT

- HIGH: 400L, 4.75 hrs. runtime

### CANDELA

- HIGH: 7,964

### BEAM DISTANCE

- HIGH: 178m

### WATER RATING

- IP-67 (dustproof, waterproof)

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 7.4 in (188mm)
- WIDTH: 1.7 in X 1.3 in (33mm x 43mm)
- BEZEL DIAMETER: 2.1 in (53mm)
- WEIGHT: 9.9 oz (280g)

### BATTERY

- Integrated Li-ion battery (included)

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Light with battery
- Lanyard
- Charger
- AC & DC cords

| FL 1 STANDARD  | FLASH                | FLOOD                | DUAL-LIGHT           |
|--|----------------------|----------------------|----------------------|
|  | <b>240</b><br>LUMENS | <b>175</b><br>LUMENS | <b>400</b><br>LUMENS |
|  | <b>8h</b>            | <b>8h 30min</b>      | <b>4h 45min</b>      |
|  | <b>178m</b>          |                      |                      |
|  | <b>7964cd</b>        |                      |                      |
|  |                      |                      |                      |
|  |                      |                      |                      |

#### Model LXPR-5522GMX

Permissible Flashlight Assembly

APPROVAL No. 20-A160002-0



TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

- WARNINGS: 1) MSHA approved for use with one part number L5522-BATT rechargeable battery pack only.  
 2) The Model LXPR-5522GMX Safety Flashlight is only to be charged on the surface, or underground in accordance with the applicable regulations pertaining to battery-charging stations (reference 30 CFR 75.340) with a Bayco Products, Inc. model L5522-CHGR1.  
 3) Do not open in areas where permissibility is required.

ATENÇÃO - UTILIZAR SOMENTE BATERIAS L5522-BATT.

ATENÇÃO - NÃO SUBSTITUIR A BATERIA QUANDO UMA ATMOSFERA EXPLOSIVA PUDE ESTAR PRESENTE.

ATENÇÃO - NÃO RECARREGUE A BATERIA EM ÁREAS CLASSIFICADAS.



CLASS I DIV 1 GRPS A-D T3  
 CLASS II DIV 1 GRPS E-G Class III T200°C  
 CLASS I ZONE 0 AEx ia IIC T3 Ga  
 CLASS II ZONE 20 GRP IIC  
 Ⓢ II 1 G Ex ia op is IIC T3 Ga  
 INTRINSICALLY SAFE  
 SECURITE INTRINSEQUE



Intertek ITS 16 ATEX201022X  
 ITS21UKEX0267X  
 IECEX ITS 16.0045X  
 -10°C ≤ Tamb ≤ +40°C IP54  
 3.7V/Cell  
 Input entity parameters for charging contacts on flashlight:  
 U, 4.75V  
 I, 500mA L, 0.0uH  
 P, 0.59W C, 0.0uF



#### CERTIFIED

