

# CAPM-307C



SCAN OR  
CLICK FOR:



QR-CAT-PAPR

PAPR Catalogue  
Section



QR-CAT-FULL

Full Personal  
Safety Division  
Catalogue

## CAPM-307C TR-300+ PAPR Kit includes

- TR-302E+ Air filter unit,
- M-307 Headtop with reflective tape and flame resistant Faceseal
- M-940 Cap lamp bracket
- BT-30 Breathing Tube
- TR-970 Air flow indicator
- TR-332 Battery Pack
- TR-341A Single station Battery charger
- TR-3712E PAPR-P3 Particulate filter
- TR-371+ Filter cover
- TR-3600 Prefilter
- TR-362E Spark arrestor
- TR-325 Standard waist belt
- S1303-0166 padded bag

### Availability

SAP ID	Legacy ID	AUS	NZ	Model #	Description
7012868876	AT019494742	•	•	CAPM-307C	3M™ Versaflo™ TR-300+ PAPR kit which includes TR-302E+ Air filter unit, M-307 Headtop with flame resistant faceseal and reflective tape, M-940 cap lamp bracket, BT-30 Breathing Tube, TR-970 Air flow indicator, TR-332 Battery Pack, TR-341A Single station Battery charger, TR-3712E PAPR-P3 Particulate filter, TR-371+ Filter cover, TR-3600 Prefilter, TR-362E Spark arrestor, TR-325 Standard waist belt and S1303-0166 padded bag.



**3M Australia Pty Ltd**  
Personal Safety Division  
Bldg A, 1 Rivett Road  
North Ryde NSW 2113  
Customer Service: 1300 363 565  
Email: 3msupport.safety.au@mmm.com  
Web: www.3M.com/au/ppesafety

**3M New Zealand Ltd**  
Personal Safety Division  
94 Apollo Drive, Rosedale  
Auckland 0632  
Customer Service: 0800 252 627  
Email: 3msupport.safety.nz@mmm.com  
Web: www.3M.com/nz/ppesafety

3M and Versaflo are trademarks of 3M Company.  
© 3M 2025. All rights reserved.

# 3M™ Versaflo™ TR-300+ Powered Air Turbo

## Technical Data Sheet



### Description

The 3M™ Versaflo™ TR-300+ Powered Air Turbo is a belt-mounted air purifying device. When combined with one of the 3M approved headtops, it forms a power-assisted system for respiratory protection against particles (and nuisance odour where applicable). The TR-300+ Powered Air Turbo can be used with the following 3M headtops: S-Series & M-Series.

### Features

- Two user selectable flow rates
- Controlled airflow delivers steady flow as battery discharges or filters loads with particulates
- Display shows battery charge status, selected airflow and particulate filter loading status during use
- Audible and LED alarm signals low battery charge or low airflow
- Three filter options available:
  - TR-3712E PAPR-P3 Particulate only
  - TR-3802E PAPR-P3 Particulate plus nuisance level organic vapours\*
  - TR-3822E PAPR-P3 Particulate only nuisance acid gas \* and offers protection against hydrogen fluoride up to 10 x Occupational Exposure Limit
- Lithium ion battery with LED to indicate charge status
- Three belt options (TR-325 standard, TR-327 easy-clean and TR-326 leather) for a range of applications
- Suitable for use in decontamination shower (IP 53)

\* Nuisance level refers to concentrations below the Occupational Exposure Limit

### Standards

The TR-300+ Powered Air Turbo, in combination with 3M approved headtops, has been tested and is compliant with AS/NZS 1716:2012. The TR-300+ Powered Air Turbo also meets the following requirements:

- Dust protection and protection against spraying water to EN60529 IP 53.



### Applications

The TR-300+ Powered Air Turbo, when used as part of an approved system with appropriate filters, provides protection against:

- Particles e.g. fine dusts, mists and metal fume.
- Nuisance odour levels (below the Occupational Exposure Limit) of organic vapours
- Nuisance odour levels (below the Occupational Exposure Limit) of acid gases and up to 10 x Occupational Exposure Limit of hydrogen fluoride.

The TR-300+, when used with an appropriate 3M headtop and filters, may be used in various applications including:

- Agriculture
- Chemical Industry
- Construction and Building Renovation
- Demolition
- Food and Beverage
- Medical and Healthcare
- Metalworking
- Pharmaceutical Manufacturing
- Pulp and Paper Processing
- Smelting and Foundries
- Surface Preparation
- Woodworking

## Materials

Component	Material
Turbo body	Acrylonitrile butadiene styrene (ABS)
Filter cover	Acrylonitrile butadiene styrene (ABS)
Battery casing	Acrylonitrile butadiene styrene (ABS)
Belts	TR-325 Standard polyester web belt TR-325 Polyurethane coated polyester easy-clean belt TR-325 Leather belt

## Limitations

The TR-300+ Powered Air Turbo should not be used in the following conditions:

- In atmospheres containing less than 19,5 % oxygen
- Confined spaces (lack of ventilation)
- When the risk is considered to be Immediately Dangerous to Life or Health (IDLH).
- Where the contaminant concentration is above the Occupational Exposure Limit defined for the headtop used (see relevant User Instructions for the headtop)

## Product Range

TR-300+ Powered Air Turbo is available to buy as:

- TR-302E+ Turbo Unit (includes filter cover, airflow indicator and spark arrestors)
- TR-315A+ Starter Kit (includes TR-302E+ Air filter unit, BT-30 Breathing Tube, TR-970 Air flow indicator, TR-332 Battery Pack, TR-341A Single station Battery charger, TR-3712E PAPR-P3 Particulate filter, TR-371+ Filter cover, TR-3600 Prefilter, TR-362E Spark arrestor and TR-325 Standard waist belt. Does not include a headtop/hood which is required to be purchased separately)



## Technical specifications

**Required Minimum Protection Factor (RMPF):** Depends on 3M headtop used.

### Particulate Protection Factors

All M-Series and S-Series  
Headtops and Hoods 50

### Outlet Flow Characteristics

Stated manufacturer's  
Minimum Design Flow  
(MMDF) 170l/min

Standard Flow 185 l/min +/- 10 l/min

High Flow 205 l/min +/- 10 l/min

### Battery Duration (with new filter and new battery)

High-capacity battery Standard Flow 9-12 hours

High Flow 9-10 hours

### Battery Charge Time

High capacity battery pack less than 3.5 hours

Storage conditions -30°C to +50°C < 90 %RH

Operating temperature -10°C to +55°C

Shelf Life\* 5 years from date of  
manufacture

Weight (including high  
capacity battery, belt and  
filter) Approx. 1135 g

\*The shelf life as defined above remains an indicative and maximum data, subject to many external and non controllable factors. It may never be interpreted as a warranty.

## Compatible Hoods and Headtops



## Ordering Information

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7012909223 (AU) 7012761525 (NZ)	AT010590241 (AU) XA010037779 (NZ)	•	•	TR-315A+	TR-300+ Versaflo Starter kit which includes TR-302E+ Air filter unit, BT-30 Breathing Tube, TR-970 Air flow indicator, TR-332 Battery Pack, TR-341A Single station Battery charger, TR-3712E PAPR-P3 Particulate filter, TR-371+ Filter cover, TR-3600 Prefilter, TR-362E Spark arrestor and TR-325 Standard waist belt. Does not include a headtop/hood which is required to be purchased separately
7100123725	UU008566075	•	•	TR-302E+	3M™ Versaflo™ Powered Air Turbo Unit TR-302E+, 1 ea/Case



TR-3712E  
PAPR-P3



TR-3802E  
PAPR-P3 with nuisance\* OV



TR-3822E  
PAPR-P3 with nuisance\* AG



TR-3600



TR-362E



QR-TR3-FLTR

Scan or Click for  
Tech Data Sheet

**Filters**

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7000059880	AT010592650 (AU) CR180811422 (NZ)	•	•	TR-3600	3M™ Versaflo™ TR-300+ Prefilter, TR-3600, 1/case
7100266123	UU011647516	•	•	TR-3712E	3M™ Versaflo™ Filter PAPR-P3, TR-3712E
7100018809	78815069386	•	•	TR-3802E	3M™ Versaflo™ Filter PAPR-P3 with Nuisance* Organic Vapour, TR-3802E
7100018861	78815069394	•	•	TR-3822E	3M™ Versaflo™ PAPR-P3/HF/Nuisance* Level Acid Gas Filter TR-3822E, for 3M™ Versaflo™ TR-300 Turbo Series, 1 Filter/Car, 5 Car/Case
7000103970	XA007706659	•	•	TR-362E	3M™ Versaflo™ Spark Arrestor TR-362E, 1/Car, 1 Carton/Case

\* Nuisance levels are those levels below the SafeWork Australia Workplace Exposure Limits (WEL) and WorkSafe New Zealand Workplace Exposure Standards (WES)



BT-20 S/L



BT-30



BT-40



QR-PSA-BT

Scan or Click for  
Tech Data Sheet

**Breathing Tubes**

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7100296133	70071767472	•		BT-20L	3M™ Versaflo™ Breathing Tube BT-20L, Medium/Large, 1 ea/Case. Fixed length lightweight Polyurethane L=965mm
7100134625	70071533023	•		BT-20S	3M™ Versaflo™ Breathing Tube, BT-20S/37309(AAD), Small/Medium, 1 EA/Case. Short Fixed length lightweight Polyurethane L=735mm
7100006955	XA007706584	•	•	BT-30	3M™ Versaflo™ Breathing Tube, Self-adjusting, BT-30 L= 525-850
7100069524	UU003085113	•	•	BT-40	3M™ Versaflo™ Heavy Duty Breathing Tube BT-40, 1 ea/Case Fixed length Neoprene Rubber L=840mm



QR-PSA-VID

Click or Scan to visit the 3M™ Global Versaflo™ Video Library on how to install certain accessories

**Spare Parts & Accessories**

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7100006958	XA007706592	•	•	TR-325	3M™ Versaflo™ Standard Waist Belt TR-325, 1 Pack/Case
7000103972	XA007706691	•		TR-326	3M™ Versaflo™ Leather Waist Belt TR-326, 1/Case
7000103973	XA007706709	•	•	TR-327	3M™ Versaflo™ Easy-clean Waist Belt TR-327, 1 ea/Case
7100005643	XA007706568	•	•	TR-332	3M™ Versaflo™ High Capacity Battery TR-332, 60 Wh, 1 ea/Case. Run time with new battery pack, clean filter and fully charged is approx. 8-12 hours. Recharge time is <3.5 hours
7100326780	UU012578512	•	•	TR-332	3M™ Versaflo™ Battery TR-332, High Capacity, 60 Wh, 10 EA/Case (Phase In). Run time with new battery pack, clean filter and fully charged is approx. 8-12 hours. Recharge time is <3.5 hours
7012872492 (AU) 7000103977 (NZ)	AT010590274 (AU) XA007706758 (NZ)	•	•	TR-341A	3M™ Versaflo™ Battery Charger, Single Station TR-341A, 1 Kit/Case
7100349759	UU013206378	•	•	TR-342A	3M™ Versaflo™ Single Station Battery Charger Kit TR-342A, for Versaflo™ TR-300+ PAPR with power cord, 1 EA/Case (New to supersede TR-341A)
7100343210	70100401606	•	•	TR-342-3	3M™ Versaflo™ 3-Station Battery Charger Pack Only TR-342-3, for Versaflo™ TR-300+ PAPR, No power cord, 1 Pack/Case (New)
7012875388	AT010590282	•		TR-344A	3M™ Versaflo™ Quad Station Charger TR-344A 902-04-01, 1 Kit/Case includes TR-944 docking station and 4 x TR-341 single stations. Suitable for TR-332 battery
7100260719	70071765583	•	•	TR-381	3M™ Versaflo™ PAPR Cover TR-381, for TR-300+ PAPR, 10 ea/Case. Polypropylene non woven and polyester mesh. Does not include PAPR blower.
7100035832	70071618147	•		TR-626X	3M™ Versaflo™ Belt Extender TR-626X, for TR-626 High Durability Belt, 1 EA/Case
7100035834	70071618162	•	•	TR-627X	3M™ Versaflo™ Belt Extender TR-627X/37346(AAD), for TR-627 Easy Clean Belt
7100300071	UU012452437	•	•	TR-927	3M™ Versaflo™ Easy Clean Backpack TR-927, 1 ea/Case
7100035846	70071668076	•	•	TR-971	3M™ Versaflo™ Air Flow Indicator TR-971 for all Versaflo™ PAPR units with M/S-Series loose fitting headtops, 1 EA
		•	•	BPK-HD	3M™ Versaflo™ & Speedglas™ Heavy-Duty Back Pack BPK-HD. Suitable for TR-300+, TR-600, TR-800 and Adflo
7012880650	AT010601550	•	•	S1303-0166	3M™ Versaflo Storage PAPR Bag S1303-0166, 1 Bag/Case
7100099577	UU006386765	•	•	TR-371+	3M™ Versaflo™ Filter Cover TR-371+, for TR-300/TR-300+, 1 Bag/Case



QR-TRM-207C  
Scan or Click for  
Tech Data Sheet



TRM-207C



QR-TRM-307C  
Scan or Click for  
Tech Data Sheet



TRM-307C



QR-TRM-407C  
Scan or Click for  
Tech Data Sheet



TRM-407C



QR-CAPM-307C  
Scan or Click for  
Tech Data Sheet



CAPM-307C

## Ready to use TR-300+ PPR Kits

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7012890479	AT010590522	•	•	TRM-207C	3M™ Versaflo™ TR-300+ PPR Kit which includes TR-302E+ Air filter unit, M-207 Headtop with flame resistant facesal, BT-30 Breathing Tube, TR-970 Air flow indicator, TR-332 Battery Pack, TR-341A Single station Battery charger, TR-3712E PPR-P3 Particulate filter, TR-371+ Filter cover, TR-3600 Prefilter, TR-362E Spark arrestor, TR-325 Standard waist belt and S1303-0166 padded bag
7012869262	AT010590548	•	•	TRM-307C	3M™ Versaflo™ TR-300+ PPR Kit which includes TR-302E+ Air filter unit, M-307 Headtop with flame resistant facesal, BT-30 Breathing Tube, TR-970 Air flow indicator, TR-332 Battery Pack, TR-341A Single station Battery charger, TR-3712E PPR-P3 Particulate filter, TR-371+ Filter cover, TR-3600 Prefilter, TR-362E Spark arrestor, TR-325 Standard waist belt and S1303-0166 padded bag.
7012875691	AT010590563	•	•	TRM-407C	3M™ Versaflo™ TR-300+ PPR Kit which includes TR-302E+ Air filter unit, M-407 Headtop with flame resistant shroud, BT-30 Breathing Tube, TR-970 Air flow indicator, TR-332 Battery Pack, TR-341A Single station Battery charger, TR-3712E PPR-P3 Particulate filter, TR-371+ Filter cover, TR-3600 Prefilter, TR-362E Spark arrestor, TR-325 Standard waist belt and S1303-0166 padded bag
7012868876	AT019494742	•	•	CAPM-307C	3M™ Versaflo™ TR-300+ PPR kit which includes TR-302E+ Air filter unit, M-307 Headtop with flame resistant facesal and reflective tape, M-940 cap lamp bracket, BT-30 Breathing Tube, TR-970 Air flow indicator, TR-332 Battery Pack, TR-341A Single station Battery charger, TR-3712E PPR-P3 Particulate filter, TR-371+ Filter cover, TR-3600 Prefilter, TR-362E Spark arrestor, TR-325 Standard waist belt and S1303-0166 padded bag.

## 3M Versaflo TR-300+, TR-600 and TR-800 Comparison Chart

	3M™ Versaflo™ TR-300+ PAPR	3M™ Versaflo™ TR-600 PAPR	3M™ Versaflo™ TR-800 PAPR
			
<b>Availability</b>	AU & NZ	AU & NZ	AU & NZ
<b>Blower part no.</b>	TR-302E+	TR-602E	TR-802E
<b>AS/NZS 1716 Approved configurations</b>	Yes	Yes	Yes
<b>PAPR-P3 Filter</b>	TR-3712E	TR-6710ANZ	TR-6710ANZ
<b>Pre-Filter</b>	TR-3600	TR-6600	TR-6600
<b>Spark Arrestor</b>	TR-362	TR-662	TR-662
<b>Gas and Vapour Cartridges</b>	No	TR-6310ANZ PAPR-A1P3 TR-6580ANZ PAPR-A1B1E1HgP3	TR-6310ANZ PAPR-A1P3 TR-6580ANZ PAPR-A1B1E1HgP3
<b>Nuisance Level<sup>6</sup></b>	TR-3802E Organic Vapour TR-3822E Acid Gas	TR-6820ANZ Organic Vapour & Acid Gas	TR-6820ANZ Organic Vapour & Acid Gas
<b>Battery Run Time<sup>1</sup> (~ hours) &amp; Watt Hour (WH)</b>	TR-332: 8-12 60 Wh	TR-630: 4 - 12, 60 Wh TR-632: 7 - 19, 91 Wh	TR-830: 4 - 8 44 Wh
<b>Battery Charge Time (~ hours)</b>	<3.5	< 3.5 hrs (TR-630) <4.5 hrs (TR-632)	<4
<b>Chargers*</b>	TR-341A Single TR-344A 4-Unit TR-342A	TR-641A Single TR-644A 4-Unit TR-642A	TR-641A Single TR-644A 4-Unit TR-642A
<b>Approximate Airflow (Loose Fitting)</b>	Std: 185 lpm High: 205 lpm	Std: 185 lpm Med: 205 lpm High: 225 lpm	Std: 185 lpm Med: 205 lpm High: 225 lpm
<b>Approximate Airflow (Tight Fitting)</b>	NA	Std: 135 lpm Med: 150 lpm High: 170 lpm	Std: 135 lpm Med: 150 lpm High: 170 lpm
<b>Cleaning (blower only)</b>	Wipe down only	Wipe down, or rinse or submerge with use of TR-653 Cleaning & Storage Kit	Wipe down, or rinse or submerge with use of TR-653 Cleaning & Storage Kit
<b>Ingress Protection</b>	IP-53 Rating in use <sup>2</sup>	IP-54 Rating in use <sup>3</sup> IP-67 with cleaning & storage kit in place <sup>7</sup>	IP-54 Rating in use <sup>3</sup> IP-67 with cleaning & storage kit in place <sup>7</sup>
<b>Elevation Limits</b>	-610 m to 4300 m	-610 m to 5000 m	-610 m to 5000 m
<b>Belt and Backpack Options*</b>	TR-325 Standard Belt TR-326 High Durability Belt TR-327 Easy Clean Belt BPK-HD Backpack TR-927 Backpack TR-626X Extender TR-627X Extender	TR-626 High Durability Belt TR-627 Easy Clean Belt BPK-HD Backpack TR-927 Backpack TR-626X Extender TR-627X Extender	TR-626 High Durability Belt TR-627 Easy Clean Belt BPK-HD Backpack TR-927 Backpack TR-626X Extender TR-627X Extender
<b>Blower Alarms</b>	Visual/Audible	Visual/Audible/Vibratory	Visual/Audible
<b>User Interface</b>	Battery charge, filter loading and airflow status alarm	Battery charge, filter loading and airflow status alarm	Battery charge, filter loading and airflow status alarm
<b>Battery Cycles</b>	Approx. 500 – Full charge/discharge cycles equivalents until 80% of the original capacity over the course of the first year of service when used under recommended conditions	Approx. 500 – Full charge/discharge cycles equivalents until 80% of the original capacity over the course of the first year of service when used under recommended conditions	Approx. 750 – Full charge/discharge cycles equivalents until 80% of the original capacity over the course of the first year of service when used under recommended conditions

\*Refer to code sections for further information on country availability.

	<b>3M™ Versaflo™ TR-300+ PAPR</b>	<b>3M™ Versaflo™ TR-600 PAPR</b>	<b>3M™ Versaflo™ TR-800 PAPR</b>
<b>Battery Type</b>	Lithium Ion	Lithium Ion	Lithium Ion
<b>Headtops*</b>	M-Series, S-Series	M-Series, S-Series, Selected Tight-fitting styles (bayonet style)	M-Series, S-Series, Selected Tight-Fitting (bayonet style)
<b>Breathing Tubes (Loose Fitting)*</b>	BT-20S, BT-20L, BT-30, BT-40	BT-20S, BT-20L, BT-30, BT-40	BT-20S, BT-20L, BT-30, BT-40
<b>Breathing Tubes (Tight Fitting)*</b>	NA	BT-63 BT-64	BT-63 BT-64
<b>Approximate Blower Weight without battery</b>	386 grams	635 grams	680 grams
<b>Approximate Battery Weight</b>	362 grams	453 grams 589 grams	680 grams
<b>Approximate Blower Dimensions with HE filter and cover</b>	20.3 cm W x 17.7 cm H x 7.6 cm D	25.4 cm W x 20.3 cm H x 7.6 cm D	25.4 cm W x 20.3 cm H x 7.6 cm D
<b>Shelf Life</b>	Blower: 5 years <sup>5</sup> Battery: 1 year <sup>4</sup> PAPR Filter: 5 years	Blower: 5 years <sup>5</sup> Battery: 1 year <sup>4</sup> PAPR Filter: 5 years	Blower: 5 years <sup>5</sup> Battery: 6 months <sup>4</sup> PAPR Filter: 5 years
<b>Intrinsically Safe</b>	No	No	Yes - Blower with battery certified to UL/IEC 60079 (2013) and SIMTARS IECEx SIM 19.0013

\*Refer to code sections for further information on country availability

- Estimated system run time based on testing with a new battery and a new clean filter at 20°C (68°F). Actual system run time may be extended or shortened depending on system configuration and environment.
- Suitable for use in a decontamination shower with a spray angle of up to 60 degrees from vertical
- The IP54 rating indicates the unit is protected against infiltration of dusts and water splash that would interfere with normal operation
- Battery packs should be charged immediately and fully upon receipt. TR-300+ and TR-600 batteries should be recharged after each use and at least every 9-12 months. TR-800 battery should be recharged after each use and at least every 6 months.
- The motor must be run for at least 5 minutes annually to ensure proper lubrication and operation
- Nuisance level refers to concentrations not exceeding Workplace Exposure Standard/Limit (WES/WEL)
- The IP67 rating indicates the unit is protected against infiltration of dusts and can now be rinsed under running water, immersed, or put in a respirator washer for further cleaning as long as the 3M™ Cleaning and Storage Kit TR-653 inlet and outlet plugs are installed.

## Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



## Technical Statement

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards. Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.



**3M Australia Pty Ltd**  
Personal Safety Division  
Bldg A, 1 Rivett Road  
North Ryde NSW 2113  
Customer Service: 1300 363 565  
Email: [3msupport.safety.au@mmm.com](mailto:3msupport.safety.au@mmm.com)  
Web: [www.3M.com/au/ppesafety](http://www.3M.com/au/ppesafety)

**3M New Zealand Ltd**  
Personal Safety Division  
94 Apollo Drive, Rosedale  
Auckland 0632  
Customer Service: 0800 252 627  
Email: [3msupport.safety.nz@mmm.com](mailto:3msupport.safety.nz@mmm.com)  
Web: [www.3M.com/nz/ppesafety](http://www.3M.com/nz/ppesafety)

3M and Versaflo are trademarks of 3M Company.  
© 3M 2025. All rights reserved.

# 3M™ Versaflo™ M-300 Helmet

## Technical Data Sheet

ID 2410123  
RID 618731

### Description

A lightweight air supplied helmet that provides respiratory, eye, face and head protection when suitably connected to an AS/NZS 1716 compliant air supply system.

### Features

- Lightweight, with excellent balance
- Fully-adjustable suspension that includes textile straps for optimal fit and weight distribution
- M-300 headtop offers head protection to AS/NZS 1801
- Multiple size adjustment options allow for a comfortable fit
- An air deflector allows users to direct the airflow down or into the face for increased control and comfort
- Visor design combines excellent peripheral and downward vision with good optical clarity
- Coated polycarbonate visor provides added chemical and scratch resistance and high impact protection
- QRS (Quick Release Swivel) breathing tubes allow fast and easy snap on/off connection
- Easily removable parts allow simple cleaning, maintenance and replacement
- Most user interface/adjustment points highlighted in blue for convenience
- To suit a wide range of needs, industries and applications,
- 3M™ Versaflo™ M-Series headtops offer faceseals and shrouds in various fabrics
- Accessories include ear-muffs, peel-off's, various head covers and a cap lamp bracket
- A length-adjusting breathing tube is also available
- Many parts are common to all 3M™ Versaflo™ M-Series headtops, meaning reduced inventories and downtime

### Applications

There are many workplace applications, including:

- Construction
- Grinding
- Foundries
- Heavy Industry
- Metal Fabrication
- Recycling
- Processing plants



M-307

M-307CAP

Suitable for use with TR-800 Turbo Unit, TR-300+ Turbo Unit, PF-600E-ASB, TR-600 Turbo unit and supplied air 3M Regulating V-Series Regulators and Valves

### Compatible with

#### PAPR



TR-300+



TR-600



TR-800



PF-600E-ASB with PF-949 Breathing Tube adaptor. PAPR-P1 Combination rated.

#### Continuous Flow Supplied Air



V-500E



V-100



V-200



V-300

## Standards

The M-Series headtops meet the performance requirements of Australian/New Zealand Standards AS/NZS 1716:2012:

- when connected to the 3M™ TR-800, TR-600, TR-300+ and PF-600E-ASB.
- when connected to the 3M™ Air Regulating Valve or 3M™ Vortex™ Regulators.

AS/NZS 1337.1 compliant high impact eye/face protection.

AS/NZS 1801 Type 1 Industrial Safety Helmet.

AS/NZS 1270 when fitted with optional earmuffs.

## Operation/Cleaning

Users need to be trained in the safe operation of this equipment. Routine checks must be carried out in accordance with the user instructions. Cleaning should also only be carried out as specified in the user instructions.

## Specifications

Versaflo™ M-300 Helmet	
Weight	832g (without breathing tube)
Storage Conditions	-30°C to +50°C and <90% humidity
Operating Temperature	-10°C to +55°C and <90% humidity

## Ordering Information

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7100257937	UU011469960	●		M-306	3M™ Versaflo™ M-Series Helmet with Comfort Faceseal, M-306, 1 ea/Case
7000052874	70071562006	●	●	M-307	3M™ Versaflo™ Respiratory Hard Hat Assembly M-307, with Premium Visor and Faceseal, 1 EA/Case
7012888431	AT019494759	●	●	M-307CAP	3M™ Versaflo™ High Impact Helmet M-307 with M-940 Cap Lamp Bracket, 1 ea/Case



BT-20 S/L



BT-30



BT-40



QR-PSA-BT

Scan or Click for Tech Data Sheet

## Breathing Tubes

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7100296133	70071767472	●		BT-20L	3M™ Versaflo™ Breathing Tube BT-20L, Medium/Large, 1 ea/Case. Fixed length lightweight Polyurethane L=965mm
7100134625	70071533023	●		BT-20S	3M™ Versaflo™ Breathing Tube, BT-20S/37309(AAD), Small/Medium, 1 EA/Case. Short Fixed length lightweight Polyurethane L=735mm
7100006955	XA007706584	●	●	BT-30	3M™ Versaflo™ Breathing Tube, Self-adjusting, BT-30 L= 525-850
7100069524	UU003085113	●	●	BT-40	3M™ Versaflo™ Heavy Duty Breathing Tube BT-40, 1 ea/Case Fixed length Neoprene Rubber L=840mm

## Technical Statement

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards. Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.



QR-PSA-VID

Click or Scan to visit the 3M™ Global Versaflo™ Video Library on how to install certain accessories



### Spare Parts & Accessories

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7000042895	70071564218	•	•	M-316	3M™ Versaflo™ Airflow Deflector, M-316, 1/case
7000030034	70071564226	•	•	M-350	3M™ Versaflo™ Head Suspension, M-350, 1/case
7100063941	UU003029749	•	•	M-354	3M™ Versaflo™ Forehead Seal M-354, 1 ea/Case
7000042899	70071564309	•	•	M-919	3M™ Versaflo™ M-Series Visor Frame Buttons M-919, 10 ea/Case
7000030038	70071564317	•	•	M-920	3M™ Versaflo™ Visor Frame Assembly, M-920, 1/case
7000042900	70071564325	•	•	M-921	3M™ Versaflo™ Visor Gasket, M-921, 5/case
7100288242	70071767332	•	•	M-924-25	3M™ Versaflo™ Tinted Peel-Off Covers M-924, for M-927 Premium Visor, 25 ea/Case
7000052876	UU003029442	•	•	M-927	3M™ Versaflo™ Premium Visor M-927/37324(AAD), 5 EA/Case
7100001829	70071564341	•	•	M-928	3M™ Versaflo™ Peel-Off Visor Covers M-928, 40 ea/Case
7100064141	UU003029202	•	•	M-935	3M™ Versaflo™ M-Series Standard Faceseal M-935, 5 ea/Case
7100137904	UU008294835	•	•	M-936	3M™ Versaflo™ Comfort Faceseal M-936, 5 ea/Case
7100137903	70071564374	•	•	M-937	3M™ Versaflo™ Faceseal, Flame Resistant M-937, 5 ea/Case
7100265324	70071766334	•	•	M-940	3M™ Versaflo™ Mining Lamp Bracket Kit M-940, for M-Series Hard Hats and Helmets, 1 ea/Case
7000044488	52000183096	•	•	M-953	3M™ Versaflo™ M-Series Helmet Headband Back Part Ratchet M-953, 1 Each/Bag, 20 Bag/Case
7100064142	UU003029772	•	•	M-956	3M™ Versaflo™ M-Series Size Reducing Ratchet Comfort Pad M-956, 10 ea/Case

7000103918	XA007705925	•	•	M-957	3M™ Versaflo™ Forehead Comfort Pad M-957, 10 Pair/Pack, 10 Pack/Case
7010604274	JH200201418	•	•	M-959	3M™ Versaflo™ Chinstrap M-959 for M-200/M-300/M-400 Helmet, 1 EA/Case
7000042905	70071564390	•	•	M-960	3M™ Versaflo™ Visor Pivot Kit, M-960, 1/case
7100063882	UU003029434	•	•	M-972	3M™ Versaflo™ Flame Resistant Headtop Cover M-972, 1 ea/Case
7100099853	UU006077661	•	•	M-973	3M™ Versaflo™ Radiant Heat Cover, M-973, 1 EA/Case
7100063944	UU003029780	•	•	M-976	3M™ Versaflo™ Head, Neck and Shoulder Cover M-976, 1 ea/Case
7000103752	XA007702625	•	•	Z3AF/2	3M™ Versaflo™ Back Plate Kit Z3AF/2, Left and Right, Helmet Adapter for M-200/M-300, 20 ea/Case
7100099097	UU008014308	•	•	MT7V/1	3M™ PELTOR™ Boom Microphone MT7V/1, 20 ea/Case
7100098955	UU008013581	•	•	MT53V/1	3M™ PELTOR™ Boom Microphone MT53V/1, 20 ea/Case



TRM-307C



CAPM-307C



QR-TRM-307C

Scan or Click for Tech Data Sheet



QR-CAPM-307C

Scan or Click for Tech Data Sheet

### Ready to use M-300 PAPR & Continuous Flow Supplied Air Kits

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7012869262	AT010590548	•	•	TRM-307C	3M™ Versaflo™ TR-300+ PAPR Kit which includes TR-302E+ Air filter unit, M-307 Headtop with flame resistant facesal, BT-30 Breathing Tube, TR-970 Air flow indicator, TR-332 Battery Pack, TR-341A Single station Battery charger, TR-3712E PAPR-P3 Particulate filter, TR-371+ Filter cover, TR-3600 Prefilter, TR-362E Spark arrestor, TR-325 Standard waist belt and S1303-0166 padded bag.
7012868876	AT019494742	•	•	CAPM-307C	3M™ Versaflo™ TR-300+ PAPR kit which includes TR-302E+ Air filter unit, M-307 Headtop with flame resistant facesal, M-940 cap lamp attached and reflective tape, BT-30 Breathing Tube, TR-970 Air flow indicator, TR-332 Battery Pack, TR-341A Single station Battery charger, TR-3712E PAPR-P3 Particulate filter, TR-371+ Filter cover, TR-3600 Prefilter, TR-362E Spark arrestor, TR-325 Standard waist belt and S1303-0166 padded bag.

SCAN OR CLICK FOR:



QR-CAT-PAPR

PAPR Catalogue Section



QR-CAT-CFSA

Continuous Flow Supplied Air Catalogue Section



QR-CAT-FULL

Full Personal Safety Division Catalogue

# 3M™ High Heat Accessories for 3M™ Versaflo™ M-300 and M-400 Helmets

The 3M™ Radiant Heat Covers M-973/M-975 when used in combination with the 3M™ M-967 Over-Visor offers 360° coverage of the 3M™ Versaflo™ M-300 / M-400 Helmets. Protection in accordance with EN ISO 11612:2015, EN 166:2001, EN 170:2002 and EN 171:2002 is offered against radiant heat and sparks/splashes for all parts of the helmet.

## Features and Benefits:

- Designed to be robust and durable to withstand some of the harshest environments experienced in the metal production industry
- Adaptable - the radiant heat cover and overvisor components are fully modular allowing the user to create multiple combinations and different coverage levels to adapt the unit to their specific needs and environment
- Low profile, designed specifically for use with 3M™ Versaflo™ M-300 / M-400 Helmets
- The flip-up over-visor design provides the user with the flexibility of shaded IR/UV protection when needed and the peace of mind of clear vision when not required
- Utilises the 3M™ Visor Carrier M-961 to fit to the 3M™ Versaflo™ M-300 / M-400 Helmets
- Optional 3M™ Radiant Heat Breathing Tube Cover BT-927 also available



## Typical Industries:

- Metalworking
- Foundries
- Glass industry
- Ceramic / porcelain industry
- Refractory product industry



**M-400 with M-975 Radiant Heat Cover with M-967 Gold Over Visor**



**3M™ Gold Over Visor M-967**



**3M™ Over Visor Frame M-961**



**3M™ Radiant Heat Cover M-973 for M-300**



**3M™ Radiant Heat Cover M-975 for M-400**



**3M™ Breathing Tube Radiant Heat Cover BT-927**

Radiant Heat Cover Performance	
EN ISO 11612 Code letter and classification Heat transmission performance requirement	
A1	Limited flame spread
B1	Convective heat
C4	Radiant heat
D3	Molten aluminium splash
E3	Molten iron splash

Gold Over Visor and Over Visor Frame Performance							
Model	European standard	Scale number	Optical class	Symbol	Field of use	Mechanical strength	
M-967 Gold Over Visor	EN 166:2001		1	BT	High speed particles	Medium energy impact at extremes of temperature	
					9		Molten metal splash
					EN 170:2002		2-5 (UV)
	EN 171:2002	4-5 (IR)					
M-961 Over Visor Frame	EN 166:2001			BT	High speed particles	Medium energy impact at extremes of temperature	
					9		Molten metal splash

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7100099853	UU006077661	•	•	M-973	3M™ Versaflo™ Radiant Heat Cover, M-973
7100099910	UU006081861	•	•	M-961	3M™ Versaflo™ Over-visor Frame M-961, 1 ea/Case
7100099909	UU006081887	•	•	M-967	3M™ Versaflo™ Over-visor, Gold, IR Shade 5, M-967
7100099854	UU006077679	•	•	M-975	3M™ Versaflo™ PAPR Radiant Heat Cover M-975, for M-400, 1 ea/Case
7100099908	UU006081895	•	•	BT-927	3M™ Versaflo™ Breathing Tube Radiant Heat Cover BT-927, 1 ea/Case



## 3M™ M-Series Headgear Assemblies Comparison Chart

	M-206	M-207	M-306	M-307 & M-307CAP	M-406	M-407
<b>Availability</b>	AU	AU & NZ	AU & NZ	AU & NZ	AU & NZ	AU & NZ
<b>Style</b>	Loose fitting facepiece faceshield	Loose fitting facepiece faceshield	Loose fitting facepiece helmet	Loose fitting facepiece helmet	Loose fitting facepiece helmet with shroud	Loose fitting facepiece helmet with shroud
<b>Air sources approved with*</b>	V-Series (V-100, V-200, V-300, V-500E) TR-300+ TR-600 TR-800 PF-600E-ASB	V-Series (V-100, V-200, V-300, V-500E) TR-300+ TR-600 TR-800 PF-600E-ASB	V-Series (V-100, V-200, V-300, V-500E) TR-300+ TR-600 TR-800 PF-600E-ASB	V-Series (V-100, V-200, V-300, V-500E) TR-300+ TR-600 TR-800 PF-600E-ASB	V-Series (V-100, V-200, V-300, V-500E) TR-300+ TR-600 TR-800	V-Series (V-100, V-200, V-300, V-500E) TR-300+ TR-600 TR-800
<b>Eye and Face Protection</b>	AS/NZS 1337.1 Eye & Face Protection - High Impact					
<b>Head Protection</b>	EN 812:2012 (Bumpcap protection)	EN 812:2012 (Bumpcap protection)	AS/NZS 1801 Occupational Protective Helmets - Type 1	AS/NZS 1801 Occupational Protective Helmets - Type 1	AS/NZS 1801 Occupational Protective Helmets - Type 1	AS/NZS 1801 Occupational Protective Helmets - Type 1
<b>Optional Hearing Protection</b>	AS/NZS 1270 Hearing Protectors	AS/NZS 1270 Hearing Protectors	AS/NZS 1270 Hearing Protectors	AS/NZS 1270 Hearing Protectors	Not applicable	Not applicable
<b>Visor</b>	M-925 standard visor	M-927 premium visor	M-925 standard visor	M-927 premium visor	M-925 standard visor	M-927 premium visor
<b>Visor Material</b>	Polycarbonate	Coated Polycarbonate (silicone hard coat)	Polycarbonate	Coated Polycarbonate (silicone hard coat)	Polycarbonate	Coated Polycarbonate (silicone hard coat)
<b>Face Seal or Shroud</b>	M-936 comfort face seal	M-937 flame resistant face seal	M-936 comfort face seal	M-937 flame resistant face seal	M-448 High Durability outer shroud; M-444 inner collar	M-447 flame resistant outer shroud; M-444 inner collar
<b>Face Seal or Shroud Material</b>	Polyurethane coated knitted polyamide	Flame retardant coated polyester	Polyurethane coated knitted polyamide	Flame retardant coated polyester	<u>Outer shroud:</u> High Durability Polyurethane coated knitted polyamide <u>Inner collar:</u> Polyurethane coated knitted polyamide	<u>Outer shroud:</u> Nomex® IIIA fabric <u>Inner collar:</u> Polyurethane coated knitted polyamide
<b>Visor Area (approx.)</b>	426 sq. cm	426 sq. cm	426 sq. cm	426 sq. cm	426 sq. cm	426 sq. cm
<b>Visor Thickness (approx.)</b>	<u>Center:</u> 2.3 mm <u>Edge:</u> 1.3 mm	<u>Center:</u> 2.3 mm <u>Edge:</u> 1.3 mm	<u>Center:</u> 2.3 mm <u>Edge:</u> 1.3 mm	<u>Center:</u> 2.3 mm <u>Edge:</u> 1.3 mm	<u>Center:</u> 2.3 mm <u>Edge:</u> 1.3 mm	<u>Center:</u> 2.3 mm <u>Edge:</u> 1.3 mm
<b>Maximum Size Range<sup>2</sup> Circumference</b>	51-64 cm	51-64 cm	51-64 cm	51-64 cm	51-64 cm	51-64 cm
<b>Approx. Weight<sup>3</sup> g</b>	624 g	626 g	850 g	857 g	1049 g	1190 g
<b>Headgear Shell</b>	HDPE (High density polyethylene)	HDPE (High density polyethylene)	PC/PBT alloy (polycarbonate/polybutylene terephthalate)	PC/PBT alloy (polycarbonate/polybutylene terephthalate)	PC/PBT alloy (polycarbonate/polybutylene terephthalate)	PC/PBT alloy (polycarbonate/polybutylene terephthalate)
<b>Headband</b>	M-150 TPE (Thermoplastic elastomer)	M-150 TPE (Thermoplastic elastomer)	M-350 TPE (Thermoplastic elastomer)	M-350 TPE (Thermoplastic elastomer)	M-350 TPE (Thermoplastic elastomer)	M-350 TPE (Thermoplastic elastomer)
<b>Visor Frame</b>	PC/PBT alloy (polycarbonate/polybutylene terephthalate)					
<b>Visor Gasket (M-921)</b>	TPE (Thermoplastic elastomer)					
<b>Operating Temp.</b>	-10° C to 55° C					
<b>Storage Temp.</b>	-30° C to 50° C					
<b>Natural Rubber Latex</b>	Does not contain components made from natural rubber latex					
<b>Maximum Life</b>	5 year recommended maximum life (shelf life plus in use life) for all models when stored in original packaging and according to the recommended storage conditions. User must inspect headgear prior to each use to determine usability. Consult M-Series Headgear User Instructions for more information.					

\*Refer to code sections for further information on country availability.

### Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



**3M Australia Pty Ltd**  
Personal Safety Division  
Bldg A, 1 Rivett Road  
North Ryde NSW 2113  
Customer Service: 1300 363 565  
Email: 3msupport.safety.au@mmm.com  
Web: www.3M.com/au/ppesafety

**3M New Zealand Ltd**  
Personal Safety Division  
94 Apollo Drive, Rosedale  
Auckland 0632  
Customer Service: 0800 252 627  
Email: 3msupport.safety.nz@mmm.com  
Web: www.3M.com/nz/ppesafety

3M and Versaflo are trademarks of 3M Company.  
© 3M 2025. All rights reserved.

# 3M™ Versaflo™ TR-300+ Filters

## Technical Data Sheet



ID 2410860  
RID 012439

### Description

The following filters are made to be used with the Versaflo™ TR-300+ Powered Air Purifying Respirator (PAPR) for protection against particulates and some nuisance concentration gases and vapours. These filters used with the TR-302E+ Powered Air Turbo are part of a respirator system compliant with the Australian/New Zealand Standard AS/NZS 1716:2012

### Application

These filters are designed to capture airborne particulates (thermally and/or mechanically generated particulates) of all sizes.

The TR-3802E and TR-3822E also have a limited capability to adsorb organic vapours (TR-3802E) or acid gas (TR-3822E). These are for use against nuisance levels of these gas/vapours ie airborne concentrations that are below the relevant Workplace Exposure Standard (WES) for the specific gas/vapours involved.

For exposures above the WES of gas/vapours, the Versaflo™ TR-600 and its associated filters should be considered.

### Protection Factors

When fitted with any of the PAPR-P3 filters, the Versaflo™ TR-300+ PAPR will give the wearer a protection factor of 50 against mechanically and thermally generated particles (AS/NZS 1715).

These PAPR products are available with a range of different headtops for various applications e.g. lightweight head coverings, hoods and headtops.

### Specifications

Filtration	>99.95% efficient (AS/NZS1716:2012)
Length	350 (mm)
Width	195 (mm)
Height	125 (mm)
Weight	1.30 (kg)
Expiry	5 years from Date of Manufacture – indicated on filter



### Compatible with



TR-300+



QR-TR300PLUS

Scan or Click for  
Tech Data Sheet



TR-3712E  
PAPR-P3



TR-3802E  
PAPR-P3 with nuisance\* OV



TR-3822E  
PAPR-P3 with nuisance\* AG



TR-371+



TR-3600



TR-362E

\* Nuisance levels are those levels below the Workplace Exposure Standards/ (WES) Workplace Exposure Limits (WEL)

### Service Life

The service life of these filters will vary according to the time of use, the selected flow rate and level of exposure to airborne particulates. There is a visual and audible alarm on the control panel of the air filter unit and an indication of current condition of the particle filter. When the filter is full a warning will sound and the filter will need to be replaced with a new one.

### Disposal

If disposal of parts is required, this should be undertaken in accordance with local health and safety and environmental regulations.

## Storage

This product should be stored in the packaging provided in dry, clean conditions, away from direct sunlight, sources of high temperature, petrol and solvent vapours. Do not store outside the temperature range -30°C to +50°C or with humidity above 90%. If the product will be stored for an extended period of time before use, the suggested storage temperature is 4°C to 38°C. Before initial use, always check that the product is within the stated shelf life (use by date).

## Before selecting a filter the following should be considered:

- Complete a risk assessment.
- Identify and measure the hazardous substances in the workplace environment.
- Compare those airborne contaminants to the relevant workplace exposure limit values.
- When selecting the correct RPE consider the properties of the hazardous substances, the needs and work of the wearer and workplace conditions.
- Does the atmosphere contain sufficient oxygen throughout the period of exposure?
- If there is insufficient oxygen or the contaminant concentrations are unknown or higher than the exposure limits then SCBA or Airline must be used.
- Responsibility for correct filter selection remains with the end user.

## Product

The following filter options are available for the TR-302E+ Powered Air Turbo's:

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7100266123	UU011647516	•	•	TR-3712E	3M™ Versaflo™ Filter PAPR-P3, TR-3712E
7100018809	78815069386	•	•	TR-3802E	3M™ Versaflo™ Filter PAPR-P3 with Nuisance O/V, TR-3802E
7100018861	78815069394	•	•	TR-3822E	3M™ Versaflo™ P/HF/Nuisance Level Acid Gas Filter TR-3822E, for 3M™ Versaflo™ TR-300 Turbo Series, 1 Filter/Car, 5 Car/Case
7000059880	AT010592650 (AU) CR180811422 (NZ)	•	•	TR-3600	3M™ Versaflo™ TR-300+ Prefilter, TR-3600, 1/case
7100099577	UU006386765	•	•	TR-371+	3M™ Versaflo™ Filter Cover TR-371+, for TR-300/TR-300+, 1 Bag/Case
7000103970	XA007706659	•	•	TR-362E	3M™ Versaflo™ Spark Arrestor TR-362E, 1/Car, 1 Carton/Case

## Limitations of use

- Do not use for respiratory protection against unknown atmospheric contaminants or when concentrations of contaminants are unknown or immediately dangerous to life or health (IDLH).
- Do not use in atmospheres containing less than 19.5% oxygen. (3M definition. Individual countries may apply their own limits on oxygen deficiency. Seek advice if in doubt).
- Do not use against contaminants with poor warning properties.
- The filter cannot be cleaned and should be replaced if excessively dirty.
- Keep inner filter seal clean. The seal can be cleaned with fresh water but ensure that water does not enter the filter.
- Never attempt to clean filters by knocking or blowing out accumulated material.

## Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



## Technical Statement

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards. Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.



**3M Australia Pty Ltd**  
Personal Safety Division  
Bldg A, 1 Rivett Road  
North Ryde NSW 2113  
Customer Service: 1300 363 565  
Email: [3msupport.safety.au@mmm.com](mailto:3msupport.safety.au@mmm.com)  
Web: [www.3M.com/au/ppesafety](http://www.3M.com/au/ppesafety)

**3M New Zealand Ltd**  
Personal Safety Division  
94 Apollo Drive, Rosedale  
Auckland 0632  
Customer Service: 0800 252 627  
Email: [3msupport.safety.nz@mmm.com](mailto:3msupport.safety.nz@mmm.com)  
Web: [www.3M.com/nz/ppesafety](http://www.3M.com/nz/ppesafety)

3M & Versaflo are trademarks of 3M Company.  
© 3M 2025. All rights reserved.

# 3M™ Versaflo™ Mining Cap Lamp Bracket Kit M-940

## Technical Data Sheet

### Product description

The 3M™ Mining Lamp Bracket Kit M-940 is designed for use on 3M™ Versaflo™ M-200 Series, M-300 Series and M-400 Series headgear, when used with an approved air source. 3M has designed the Mining Lamp Bracket M-940 to be compatible with certain cordless and corded adjustable angle mining lamps that utilize a metal retaining clip on the lamp body.

The 3M™ Mining Cap Lamp Bracket is designed to allow the lamp retaining clip to slide into the slot on the M-940 bracket. The angle of the 3M™ Mining Cap Lamp Bracket is adjustable allowing for a desired light angle. The bracket slot width is approximately 23mm wide

### Key features

- Securely holds a range of fixed and adjustable angle mining lamps
- Compatible with certain M-series hard hats and helmets – M-200, M-300 and M-400 series
- Designed for use with Versaflo™ PAPRs
- The bracket is made of a lightweight durable polymer
- Angle of the bracket is adjustable allowing for a desired lamp light angle
- Can be used with both cordless and corded mining lamps
- Easy to install
- Cleanable
- While the bracket is intended for use in mining applications, it may have uses in other applications as well, such as tunnelling, industrial, heavy manufacturing and transportation.

### Specifications

For information on installing the 3M™ Mining Lamp Bracket Kit, please refer to [video](#) on how to install the bracket.

**Before use of the 3M™ Mining Cap Lamp Bracket Kit M-940, the wearer must read and understand the User Instructions for the 3M™ Versaflo™ M-Series Headgear and the 3M™ Mining Cap Lamp Bracket Kit M-940.**



\*Does not include helmet

### Frequently asked questions

- Q:** Is the lamp bracket cleanable?  
**A:** Yes. The M-940 can be cleaned with soap and water
- Q:** What M-Series helmets can the M-940 lamp bracket be used with?  
**A:** The lamp bracket can be used with the M-200, M-300 and M-400 series hardhats and helmets.
- Q:** Can the lamp bracket be removed once it is installed?  
**A:** Yes. The lamp bracket can be removed.
- Q:** Can the lamp bracket be used with the M-Series welding helmets?  
**A:** No
- Q:** Does the M-940 kit come with a mining lamp?  
**A:** No. The mining lamp does not come in the kit.

## Mining Lamps for use with the M-940

3M has evaluated the following mining lamps and found the mounting retaining clip to be compatible with the 3M™ Mining Lamp Bracket:

Manufacturer	Model (s)
Polaris	NL8005, NL0329
Koehler Bright	Star LI 6000-G Cordless LED Cap Lamp
Optimac	HaloLite H1, HaloLite H2, MiniHalo
TJL	KL6L7M Cap Lamp
Wisdom	4A Cordless Cap Lamp, KL5M
MST	Global TRAK Orb Cordless Lamp, ICCL Model
MineARC	SiriUS Cordless Lamp
Roobuck	RN2T Cordless Lamp

3M has not evaluated all mining lamps available in the market. If intending to use a mining lamp not listed above, please evaluate the security of the mining lamp in the bracket prior to use for acceptability. 3M expects lamps with similar mounting clips to those listed above to be acceptable for use with the M-940 mining lamp bracket, however security of the lamps should always be evaluated prior to use in your environment.

The 3M Mining Lamp Bracket Kit M-940 is not designed to be used with mining lamps that require special hardware/ fasteners or adhesives to mount the lamp to the headgear. The slot on the mining lamp bracket is approximately 23mm wide. If you have any questions or concerns regarding a mining lamp with the 3M Mining Lamp Bracket Kit, please reach out to your local 3M sales representative for more information.

## Ordering Information

3M Code	Model #	Description
70071766334		M-940 Mining cap lamp bracket Kit 1 EA/CS
AT019494742		PAPR Helmet CAPM-307C complete with TR-300+, charger, M-307 Headtop, BT-30 breathing tube, TR-3712E P3 filter, padded bag and M-940 Cap lamp bracket kit.
AT019494759		M-307 Helmet with M-940 Cap lamp bracket kit



**3M Australia Pty Ltd**  
**Personal Safety Division**  
Bldg A, 1 Rivett Road  
North Ryde NSW 2113  
TechAssist Helpline: 1800 024 464  
Customer Service: 1300 363 565  
Email: techassist@mmm.com  
Web: www.3M.com/au/ppesafety

**3M New Zealand Ltd**  
**Personal Safety Division**  
94 Apollo Drive, Rosedale  
Auckland 0632  
TechAssist Helpline: 0800 364 357  
Customer Service: 0800 252 627  
Email: techassist@mmm.com  
Web: www.3M.com/nz/ppesafety

## Important Notice

The use of the 3M product, described within this document assumes that the user has previous experience of this type of product and that it will be used by a competent professional. Before any use of this product, it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environments. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the 3M product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (which cannot verify or control those elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for 3M products are determined with the sales contract documents and with the mandatory and applicable clause, excluding any other warranty or compensation.

Respiratory protection is only effective if it is correctly selected, fitted and worn throughout the time the wearer is exposed to respiratory contaminants. 3M offers advice on the selection of products, and training on the correct fitting and usage.

For more information on 3M products and services please call the 3M TechAssist Helpline -3M Australia 1800 024 464 or 3M New Zealand 0800 364 357.

3M is a trademark of 3M Company.  
Please recycle. Printed in Australia.  
© 3M 2022. All rights reserved.